



SMART ALARM SYSTEM

Search for the free 'ERA Protect' App







PROTECT FEATURES

- Access from anywhere. Access alarm from anywhere with easy-to-use App, downloadable for IOS or Android Smartphones.
- Always monitoring. The Protect alarm will continue to protect building, monitor and notify user even if in event that the internet fails.
- Built in protection. A built-in Sim will allow the user to control the system, whilst maintaining all functionality including data transfer to the cloud.
- Hassle free communicating. The 4G roaming sim
 will pick up the best signal to communicate so no
 need to choose specific provider. Full sim
 functionality is available by simply activating the
 subscription via the app.
- Easy Control. Arm, homearm or disarm with an easy to use app, remote control or keypad. All settings can be viewed and adjusted with quick slide.

KEY BENEFITS



Dual path cloud based alarm system with over-the-air updates



Connects directly to your router, not dependent on Wi-Fi signal



Upon alarm trigger, SIM card can relay images to the cloud from up to 4 cameras even if internet connection is disabled



Embedded 4G roaming SIM back-up, automatically connects to strongest network signal*



App controlled from anywhere, anytime



Alarm and cameras can be controlled by a single App**

*ERA Plus subscription required

**Cameras available separately





ORDERING DETAILS

Product: Part No.

ERA Protect Smart Alarm System SALPRWHKIT00

Additional Accessories Part No.

Wireless Siren White SALAPWHESSU
Wireless Pet PIR SALAPWHPFP
Window Door Sensor SALAPWHMAG
Wireless Remote SALAPWHREM
Wireless Keypad SALAAPWHKPR
Floodlight Camera HD SCAEFBL1080
Outdoor Camera 1080P SCAEXWH1080

TECHNICAL INFORMATION

ERA Protect Hub

Item Parameter

Power Supply: 12v DC
Internal Siren Level: 80dB
Standby Current: <100mA
Alarm current: <170mA
Wireless Devices: 96
Wi-Fi Frequency: 2.4Ghz

Wi-Fi Protocol: IEEE802.11b/g/n

Network Protocol: DHCP

Internet Access: 1 x RJ45 10M/100M 4G Module: QUECTEL EC25-E Wireless Network: 868 MHz FSK Battery Back Up: 3.7V/3000mAH Operating Temperature: -10°C ~ 60°C Dimensions (HxWxD): 150 x 150 x 30mm Housing Material: **ABS Plastic** EAN: 5054040301943

ERA Protect PIR Motion Sensor

Item Parameter

Battery: DC 3V (1x CR123A lithium

battery)

Maximum Detection

Distance: 12m/25°C

Emitting Distance: 150m (in the open area)

Working Current: ≤35mA
Quiescent Current: ≤20uA

Maximum Coverage: 12m x 12m (39 x 39 feet) / 90°

Frequency: FSK 868MHz

Pet Immunity: 25kg

Alarm Indication: LED red light flashes Launch

Heatbeat Report: Once every 2 hours

Housing Material: ABS Plastic

Operating Temperature: 10°C ~ 60°C <95% RH 20°C ~

Storage Temperature: 60°C (4°F ~ 140°F)
Dimensions (HxWxD): 78 x 51.5 x 35mm

TECHNICAL INFORMATION

ERA Protect Door / Window Sensor

Item Parameter

Power Supply: CR123 A 3V (1x lithium battery)

Static Current: <10uA Alarm Current: <35mA

Transmitting Distance: <150m (in open area)

Radio Frequency: 868 MHz Housing Material: ABS Plastic

Sensor Dimensions (LxWxH): 69.5 x 21.2 x 19.5mm Probe Dimensions (LxWxH): 34.5 x 10 x 13.2mm

ERA Protect Remote Control

Item Parameter

Power Supply: CR2450 3V (1x lithium battery)

Quiescent: ≤3uA Working Current: ≤30mA

Transmitting Distance: <100m (in open area)
Radio Frequency: 868 MHz (75±KHz)

Housing Material: ABS Plastic

Operations Condition: Temperature: -10°C ~ +60°C

Relative Humidity: <80%

(non-condensing)

Remote Dimensions (LxWxH): 58 x 31 x 9.5mm

PACKAGING

Kit Content

Includes: $1 \times \text{Hub}$, $1 \times \text{PIR}$ Motion Sensor, $1 \times \text{Door} / \text{Window}$ Sensor, $2 \times \text{Remote Controls}$, $1 \times \text{Power Supply}$, $1 \times \text{Ethernet}$

Cable, 1 x Fixing Kit, 1 x Quick Start Guide

SUGGESTED INSTALLATION

